

## Masking Tape

---



### Description:

**General Purpose** - Is a light coloured masking tape. It is conformable and flexible. This tape is designed primarily as a general purpose masking tape with strong adhesion level. Suitable for binding packaging usage and general application usage.

**Automotive Grade** - A high quality crepe paper coated with special formulated natural rubber adhesive. The 929 and 969 function during bake cycles of up to 900 for periods up to one (1) hour and easy non residue removal.

Suitable for automotive spraying industry and electronic industry such as bandoleering, electroplating and soldering usage.

**High Temperature** - Good masking performance in high temperature up to 160<sup>o</sup> celsius for 1 hour. Suitable for automotive paint masking, insulation panel and wooden window manufacturing.

---

**Mailing Address:** No. 10, Jalan SL 14/2, Bandar Sungai Long, 43000 Kajang Selangor. Malaysia

**Tel/Fax:** +603-9080 3600 **Mobile:** +6 016 369 1313

**Email :** [sales@zonsan.com](mailto:sales@zonsan.com) **Website:** <http://www.zonsan.com>

**Page:** 1 of 2

**Technical Specifications;**

Item No.	Description	Thickness (mm)	Adhesion (G/25mm)	Tensile Strength (KG/25mm)	Elongation (%)	Features
101919	General Purpose Masking Tape	0.135	750	5.5	5	General purpose crepe paper masking tape. Good for sealing, bundling & light packaging uses.
101929	Automotive Grade Masking Tape	0.15	750	3.0	5	Automotive painting, flexible and can remove with no residue. Heat resistance 100°C for 1 hour.
101939	General Purpose Masking Tape	0.145	900	4.5	10	A premium grade of general masking tape for sealing, bundling & packaging uses.
101969	Automotive Grade Masking Tape	0.130	850	305	5	Automotive painting, flexible and can remove with no residue. Heat resistance 100°C for 1 hour.
101999	High Temperature Masking Tape	0.16	1100	12	10	Good masking performance in high temperature up to 160°C.